THC Model Performance

◆ Adopted the integrated casting process and the overall seal design, with high-quality imported components for key parts, the pump doesn't leak even when the seal for pressure cylinder breaks. All the piston rods are chrome plated, which makes them good enough in the heat resistance and hardness. Unlike the scattered parts, the pump valve core with the overall design is convenient for maintenance. With the overload protection on the valve, the pump won't lift when overloaded.

THW Model Performance

◆ The steel plate welded pump lowers the cost, which makes it more economical and practical.Three–stage positioning lowering control enables the easier operation.And the pump with manual slow lowering control valve enhances the security.The tapered arc design for the front of forks reduces the deformation.

THC(W)Hand Pallet Truck Main Specifications

Model	THC20		THC25		THC30		THW20		THW25		THW30	
Rated load capacity (Kg)	2000		2500		3000		2000		2500		3000	
Min. lowered fork height (mm)	85	75	85	75	85	75	85	75	85	75	85	75
Max. lowered fork height (mm)	200	190	200	190	200	190	195	185	195	185	195	185
Steering wheel(big) (mm)	200×50	180×50	200×50	180×50	200×50	180×50	200×50	180×50	200×50	180×50	200×50	180×50
Bearing wheel single (mm)	82×93	74×93	82×93	74×93	82×93	74×93	82×93	74×93	82×93	74×93	82×93	74×93
Bearing wheel double (mm)	82×70	74×70	82×70	74×70	82×70	74×70	80×70	74×70	82×70	74×70	82×70	74×70
Single fork size (W×H)	160×50						160×60					
Fork width(outside)	540/685						550/685					
Total fork length	1150/1220											